



- *Audio prompt diagnosis on failures
- *Intelligent control and display technology.
- *comfortable airflow
- *AC/DC Power Operation
- *Maximum saving is 100%
- *Environment friendly

ADC Window Type ~On Grid

Model	TKC-26S/NH	TKC-35S/NH	TKC-52S/NH	TKC-72S/NH	
BTU	9000 BTU	12000BTU	18000BTU	24000 BTU	
Power Supply	1-220V/50Hz/60Hz and 36V DC				
Refrigerant	R22/R410A	R22/R410A	R22/R410A	R22/R410A	
Capacity	2500W/9000BTU	3500W/12000BTU	5200W/18000BTU	7200W/24000BTU	
Input Power	Cooling	600W	800W	1100W	1600W
	Heating	570W	750W	1050W	1500W
DC Input power	800W	1000W	1500W	2000W	
Current (Amp)	Cooling	2.5A	3.6A	4.8A	7.3A
	Heating	2.4A	3.4A	4.6A	7.2A
Air flow (m3/hour)	390	450	520	700	
Noise(dBA)	52-55	54-58	56-60	58-62	
Weight (Net/Gross)	31kg/33kg	42kg/44kg	45kg/47kg	52kg/55kg	
Product Dimension	450*1000*350mm	560*1100*400mm	560*1100*400mm	670*1100*455mm	
Package Dimension	550*1080*440mm	620*1180*445mm	620*1180*445mm	730*1180*500mm	
Quantity(20ft/40HQ)/pcs	110/265	90/230	90/230	70/160	